

### 12"x48"x2cm porcelain paver and pool coping

12"x48" forest natural - 280701



12"x48" porcelain pool coping with bullnose edge - natural 285701



12"x48" forest silver - 280702



12"x48" pool coping with bullnose edge - silver 285702



12"x48" forest dark - 280703



12"x48" porcelain pool coping with bullnose edge - dark 285703



12"x48" forest cherry - 280704



12"x48" porcelain pool coping with bullnose edge - cherry 285704



### Technical Data

 Thickness 2cm (19.5mm - 20.5mm) +.25% EN ISO 10545-2	 Cracking Resistance Resistant EN ISO 10545-9
 Straightness of Sides < 0.2% + 0.5% EN ISO 10545-2	 Frost Resistance Resistant EN ISO 10545-12
 Rectangularity (%) < 0.2% + 0.6% EN ISO 10545-2	 Slippery Resistance R-11 DIN 51130: 20045
 Edge & Corner Curvature < 0.2% + 0.6% EN ISO 10545-2	 Pendulum Test Dry Min. 65 Wet Min. 55 BS 7679: Parts 1-3
 Colour Variation First Quality EN ISO 10545-16	 Moisture Expansion (mm/m) < 0.3 EN ISO 10545-10
 Water Absorption < 0.1% EN ISO 10545-3	 Staining Resistance Class 5 Min. Class 3 EN ISO 10545-14
 Breaking Strength (N) > 9500N EN ISO 10545-4	 Acid & Alkali Resistance GLA EN ISO 10545-13
 Abrasion Resistance PEI III to PEI IV EN ISO 10545-7	 Household Chemicals GA Min. GB EN ISO 10545-13
 Thermal Expansion Coeff. < 9.0 x 10 <sup>-6</sup> EN ISO 10545-8	 Cadmium Release < 0.005 mg/dm <sup>2</sup> EN ISO 10545-15
 Thermal Shock Resistance Resistant EN ISO 10545-9	 Lead Release < 0.005 mg/dm <sup>2</sup> EN ISO 10545-15
 DCOF- Dry: 1.76 > 0.40 Wet: 1.75 > 0.40 BCRA ISO 10545-17	 Overall Result: positive as per TS EN 14411 standards, Annex G

### Recommended Uses

Residential & Commercial  
Floor & Wall  
Fireplaces

Interior & Exterior Freeze/Thaw  
Countertops  
Tub Surrounds & Showers